

Consew 733R-5



OVERVIEW

Extra Heavy Duty, Long Arm, Single Needle, Drop Feed, Alternating, Presser Feet, Lockstich Machine.
With: Extra Large, Long Beak, Oscillating Shuttle Hook and Bobbin, Extra High Foot Lift - (1-1/4" / 32mm), Two Row Feeder, Reverse Feed

Select Options:

APPLICATIONS

For stitching extra heavy-weight materials

Designed for such operations and products as safety and logging belts, cargo slings, buffing wheels, tents, sails, harnesses, tarpaulins and covers, fabric structures, construction barriers, parachutes, balloons, industrial bags, boot stitching, book binding

FEATURES

Synchronized upper and lower feeding mechanism assures uniform stitching

Alternating presser feet

Steel insert for take-up hinge

Reverse stitching - hand or foot operated

Stitch regulator - hand or foot operated

Presser foot lift - hand or foot operated

1-1/4 inch presser foot lift

Two row feeder

Two stitches to the inch

Stitches per minute - 550

Extra large, long-beak oscillating shuttle, hook and bobbin

Belt guard

SPECIFICATIONS

Standard or Full Function	Standard Functions
Needle	1000 or 1000H
Workspace	Standard Workspace
Hook Size	Large
Hook	35224
Feeding Mechanism	Walking Foot
Work Space	16 1/4" (413mm)
Clearance Under Presser Foot	1 1/4" (32mm)
Gross Weight	348 lbs. (158 kgs)
Stitch Type	301
Stitch Length	2 s.p.i. (13mm)
Bed Size	10" x 26 1/4" (258mm x 665mm)
Number of Needles	1 (Single)
Needle Bar Stroke	2 3/32" (53mm)
Bobbin	Pre-Wound 41
Weight	231 lbs. (105kg)
Speed, Max (S.P.M.)	550